

◆ Features:

- Point control and group available
- Reliable and safe outdoor use
- UV resistant
- IP 68 waterproof, injection molded
- Internal current stabilization (CC)
- Wide colour palette
- 5 years warranty

◆ Usage:

- Chanel letters
- Pharmacy crosses

◆ Photos:

CE





MW-MLD-PIXEL

	Model	MW-MLD-PIXEL-1WW MW-MLD-PIXEL-1NW MW-MLD-PIXEL-1W MW-MLD-PIXEL-1CW	MW-MLD-PIXEL-1R MW-MLD-PIXEL-1G MW-MLD-PIXEL-1B MW-MLD-PIXEL-1Y	MW-MLD-PIXEL-1RGB
Power	Rated voltage	12Vdc +/- 5%		
	Power consumption	0,36W		0,3W
	Power consumption of chain	18W		15W
	Q-ty of diodes in module	1		
	Color of Light	W-white (6500K) WW-white (3000K) NW-white (4000K) CW-white (9000K)	R - red G - green B - blue Y - yellow	RGB
	Flux	291m	R - 211m G - 4,51m B - 1,51m	R - 211m G - 4,51m B - 1,51m
	Light efficiency	180lm/W	-	
	Beam angle1	145°		
	Lifetime	50K hours		
Wires	Wire length	65mm		
	Wires designation	White & red (+) White (-)		
Properties	Protection	IP 68		
	Working temperature	-25°C ... 55°C		
Dimensions	Height, width, length	18x20mm 15,7(12)mm		
	Diameter	3,48mm		
Others	Housing material	ABS, PC cover		
	Q-ty of modules per 1 m	11pcs		
Packing	Chain	50pcs		
	Bag	100pcs		
	Cartoon Box	1000pcs		

◆ DIMENSIONS :

Dimensions: mm

