


# FTPC100V-E series

100W Constant Voltage LED Power Supply



## ■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Over current / Over voltage/Over temperature
- Cooling by free air convection
- Compliance to worldwide regulations for lighting



## © ELECTRICAL SPECIFICATION

MODEL	FTPC100V12-E	FTPC100V24-E
<b>OUTPUT</b>		
<b>Rated Voltage</b>	12V	24V
<b>Rated Current</b>	8.33A	4.17A
<b>Current Range</b>	0 ÷ 8.33A	0 ÷ 4.17A
<b>Rated Power</b>	100W	100W
<b>Line Regulation</b>	± 1%	± 1%
<b>Load Regulation</b>	± 0.5%	± 0.5%
<b>Voltage Tolerance [3]</b>	± 5%	± 5%
<b>Ripple &amp; Noise (max.) [2]</b>	300mV <sub>p-p</sub>	700mV <sub>p-p</sub>
<b>Setup, Rise Time [4]</b>	500ms, 50ms / 230VAC at full load	
<b>Hold up Time (typ.)</b>	10ms / 230VAC at full load	
<b>INPUT</b>		
<b>Voltage Range</b>	200 ÷ 240VAC	
<b>Frequency Range</b>	47 ÷ 63Hz	
<b>Power Factor (typ.)</b>	PF > 0.9 / 230VAC at full load	
<b>Efficiency (typ.)</b>	88%	90%
<b>AC current (typ.)</b>	0.7A / 230VAC	
<b>Inrush current (max.)</b>	75A / 230VAC (25°C)	
<b>No Load Power Consumption (max.)</b>	< 1W	
<b>PROTECTIONS</b>		
<b>Over Current</b>	Range: > 120%	
	Type: Hiccup mode. Recovers automatically after fault condition is removed.	
<b>Short Circuit</b>	Type: Hiccup mode. Recovers automatically after fault condition is removed.	
<b>Over Voltage</b>	< 18V	< 36V
	Type: shut down output voltage. Re-power on to recovery.	
<b>Over Temperature</b>	Type: Shut-off. Re-power on to recover.	

# FTPC100V-E series

100W Constant Voltage LED Power Supply



## WORKING ENVIRONMENT

<b>Working Temperature</b>	-20°C ÷ +45°C
<b>Working Humidity</b>	45 ÷ 85% RH non-condensing
<b>Storage Temperature and Humidity</b>	-30°C ÷ +70°C, 10 ÷ 95% RH non-condensing

## SAFETY AND EMC REGULATIONS

<b>Safety Standards</b>	Compliance to EN61347-1, EN61347-2-13
<b>Withstand Voltage</b>	IN/OUT: 3.75kVAC
<b>EMC Emission</b>	Compliance to EN55015
<b>EMC Immunity</b>	Compliance to EN61547
<b>Harmonic Current</b>	Compliance to EN61000-3-2, EN61000-3-3

## OTHERS

<b>Dimensions</b>	179.4 x 62.5 x 30.6mm (L x W x H)
<b>Weight and Packing</b>	0.40kg; 20pcs./box

**EAN Code**




519021351124857



519021351124864

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

## MECHANICAL SPECIFICATION



## PIN ASSIGNMENT

No.	Assignment	No.	Assignment
1	Input: AC/N/L	3	Output: U <sub>OUT</sub> -
2	Input: AC/N/L	4	Output: U <sub>OUT</sub> +