


MRS101AC3b	2 stable positions; ON-OFF; cap colour: black; SPST 2P 10A 125VAC; 6A 250VAC
MRS101AC3r	2 stable positions; ON-OFF; cap colour: red; SPST 2P 10A 125VAC; 6A 250VAC
MRS101AC3n	2 stable positions; ON-OFF; cap colour: blue; SPST 2P 10A 125VAC; 6A 250VAC
MRS101AC3o	2 stable positions; ON-OFF; cap colour: orange; SPST 2P 10A 125VAC; 6A 250VAC
MRS101AC3g	2 stable positions; ON-OFF; cap colour: green; SPST 2P 10A 125VAC; 6A 250VAC
MRS101AC3y	2 stable positions; ON-OFF; cap colour: yellow; SPST 2P 10A 125VAC; 6A 250VAC
MRS111AC3b	open cont. in non-actuated state (ON)-OFF; cap colour: black; SPST 2P 10A 125VAC; 6A 250VAC

## Specification

Rating	6A 125VAC 3A 250VAC
Contact resistance	35 mΩ max.
Insulation resistance	500 VDC 100 MΩ
Dielectric strength	1500VAC 1 min.
Operating temp.	-25~+85°C
Electrical life	10 000 cycles

## Cap marking



Cap color	
Black	<b>B</b>
White	<b>W</b>
Red	<b>R</b>
Yellow	<b>Y</b>
Green	<b>G</b>
Blue	<b>BL</b>
Orange	<b>O</b>
Gray	<b>GR</b>

Base color	
Black	<b>B</b>
White	<b>W</b>
Gray	<b>GR</b>